

# ARCTIC CAT®

## ATV RACK BAG

**Check for the following parts before beginning installation:**

1 Instruction sheet, 1 Rack Bag, 2 Foam dividers, 1 Foam stiffener

### INSTALLATION INSTRUCTIONS

1. Connect the velcro on the underside of the sewn-in stiffener to the velcro flap on the inside of the bag. Insert the foam stiffener into the top of the zippered compartment following the contour of the bag. Connect the velcro on the foam dividers to the velcro on the inside of the bag
2. Place the bag on the rack against the rack extension bar, with the handle on the bag facing away from the driver.
3. Place the "J" hooks on the appropriate bar on the rack.
4. Thread the remaining buckle with webbing. Wrap the webbing with the attached side release buckles around the bar and back into the buckle.
5. Place the velcro straps around the sides & front of the rack, and firmly secure them.



**Caution: For heavy loads or rough terrain it is recommended you use additional tie-downs. Do not carry sharp, heavy, or pointed objects, maximum carrying capacity is 25 lbs.**

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS0436OSRACK/R1

9-7-04

# ARCTIC CAT®

## ATV RACK BAG

**Check for the following parts before beginning installation:**

1 Instruction sheet, 1 Rack Bag, 2 Foam dividers, 1 Foam stiffener

### INSTALLATION INSTRUCTIONS

1. Connect the velcro on the underside of the sewn-in stiffener to the velcro flap on the inside of the bag. Insert the foam stiffener into the top of the zippered compartment following the contour of the bag. Connect the velcro on the foam dividers to the velcro on the inside of the bag
2. Place the bag on the rack against the rack extension bar, with the handle on the bag facing away from the driver.
3. Place the "J" hooks on the appropriate bar on the rack.
4. Thread the remaining buckle with webbing. Wrap the webbing with the attached side release buckles around the bar and back into the buckle.
5. Place the velcro straps around the sides & front of the rack, and firmly secure them.



**Caution: For heavy loads or rough terrain it is recommended you use additional tie-downs. Do not carry sharp, heavy, or pointed objects, maximum carrying capacity is 25 lbs.**

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS0436OSRACK/R1

9-7-04

# ARCTIC CAT®

## ATV RACK BAG

**Check for the following parts before beginning installation:**

1 Instruction sheet, 1 Rack Bag, 2 Foam dividers, 1 Foam stiffener

### INSTALLATION INSTRUCTIONS

1. Connect the velcro on the underside of the sewn-in stiffener to the velcro flap on the inside of the bag. Insert the foam stiffener into the top of the zippered compartment following the contour of the bag. Connect the velcro on the foam dividers to the velcro on the inside of the bag
2. Place the bag on the rack against the rack extension bar, with the handle on the bag facing away from the driver.
3. Place the "J" hooks on the appropriate bar on the rack.
4. Thread the remaining buckle with webbing. Wrap the webbing with the attached side release buckles around the bar and back into the buckle.
5. Place the velcro straps around the sides & front of the rack, and firmly secure them.



**Caution: For heavy loads or rough terrain it is recommended you use additional tie-downs. Do not carry sharp, heavy, or pointed objects, maximum carrying capacity is 25 lbs.**

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS0436OSRACK/R1

9-7-04