

ARCTIC CAT®

TRAILERABLE COVER- TBX / 2-UP / CRUISER

PARTS LIST: 1 Instruction sheet 1 Trailerable cover 1 Tiedown assembly

BE SURE THE MACHINE IS PROPERLY SECURED TO THE TRAILER PRIOR TO COVER INSTALLATION. ROLLING OF THE ATV WITH THE COVER INSTALLED WILL AFFECT THE FIT AND PERFORMANCE OF THE COVER!

NOTE: This cover will not accomodate significant modifications from the original shape, such as large rack extensions, rack bags, etc. Prior to cover installation it is suggested to check for harmful objects that could cause cover damage, such as points or burrs on racks, broken plastic, studs, hot pipes, etc. It is also to be sure the machine is properly secured prior to cover installation.

INSTALLATION INSTRUCTIONS-BE SURE TO INSTALL THE COVER IN THE ORDER SPECIFIED.

Loosen all straps. Drape the cover over the ATV aligning the handlebar section. Be sure the elastic is in the rear.

Pull the front of cover over rack and body molding.

Place the rear of the cover over the rear rack and over the tailight bar.

Pull excess material over footwells. Be sure the cover is pulled down as far as possible, the tighter the better.

Connect the webbing/buckle straps starting with the front. Be sure that the strap is fed under any tiedown straps that are connecting the ATV to the trailer. Repeat for the rear webbing/buckle straps. Cinch the rear webbing/buckle strap tight by grabbing the center of the webbing and pulling backward 6"-10" to gather excess slack. Periodically inspect and re-tension as necessary.

Thread the male buckles to the webbing strap from the sub-assembly kit as seen in Diagram1.

Feed the webbing/buckle strap from the sub-assembly kit under footwell, connect to the buckles sewn on the cover, and cinch tight, do so by pulling the excess webbing underneath the footwells. This will further tension the cover.

Thread the center webbing straps through the ladderlock buckles as seen in Diagram 2., cinch downward. FOR THE 2-UP model thread the strap from the sub-assembly kit to the (4) ladderlock buckles on the center rear section of the cover. This will aid in the reduction of buffeting during trailering.

Cinch all connections evenly.

WARNING: Do not trailer with the Atv installed sideways on the trailer, the cover is designed to pull with the ATV facing forward, damage to the cover or the Atv may result. Check all connections during trailering and adjust accordingly. Damage resulting from exposure to direct sunlight cannot be warrantied. For 09 Cruiser cover access the zipper panel as necessary.

WARRANTY: Your new cover is guaranteed by Arctic Cat against any defects in material and workmanship for one full year from the date of purchase. Should any problems arise, please contact your dealer. No warranty card is necessary.

ISACTRAILTBX/R1

7-17-08




Diagram 1.




Diagram 2.

ARCTIC CAT®

TRAILERABLE COVER- TBX / 2-UP / CRUISER

PARTS LIST: 1 Instruction sheet 1 Trailerable cover 1 Tiedown assembly

BE SURE THE MACHINE IS PROPERLY SECURED TO THE TRAILER PRIOR TO COVER INSTALLATION. ROLLING OF THE ATV WITH THE COVER INSTALLED WILL AFFECT THE FIT AND PERFORMANCE OF THE COVER!

NOTE: This cover will not accomodate significant modifications from the original shape, such as large rack extensions, rack bags, etc. Prior to cover installation it is suggested to check for harmful objects that could cause cover damage, such as points or burrs on racks, broken plastic, studs, hot pipes, etc. It is also to be sure the machine is properly secured prior to cover installation.

INSTALLATION INSTRUCTIONS-BE SURE TO INSTALL THE COVER IN THE ORDER SPECIFIED.

Loosen all straps. Drape the cover over the ATV aligning the handlebar section. Be sure the elastic is in the rear.

Pull the front of cover over rack and body molding.

Place the rear of the cover over the rear rack and over the tailight bar.

Pull excess material over footwells. Be sure the cover is pulled down as far as possible, the tighter the better.

Connect the webbing/buckle straps starting with the front. Be sure that the strap is fed under any tiedown straps that are connecting the ATV to the trailer. Repeat for the rear webbing/buckle straps. Cinch the rear webbing/buckle strap tight by grabbing the center of the webbing and pulling backward 6"-10" to gather excess slack. Periodically inspect and re-tension as necessary.

Thread the male buckles to the webbing strap from the sub-assembly kit as seen in Diagram1.

Feed the webbing/buckle strap from the sub-assembly kit under footwell, connect to the buckles sewn on the cover, and cinch tight, do so by pulling the excess webbing underneath the footwells. This will further tension the cover.

Thread the center webbing straps through the ladderlock buckles as seen in Diagram 2., cinch downward. FOR THE 2-UP model thread the strap from the sub-assembly kit to the (4) ladderlock buckles on the center rear section of the cover. This will aid in the reduction of buffeting during trailering.

Cinch all connections evenly.

WARNING: Do not trailer with the Atv installed sideways on the trailer, the cover is designed to pull with the ATV facing forward, damage to the cover or the Atv may result. Check all connections during trailering and adjust accordingly. Damage resulting from exposure to direct sunlight cannot be warrantied. For 09 Cruiser cover access the zipper panel as necessary.

WARRANTY: Your new cover is guaranteed by Arctic Cat against any defects in material and workmanship for one full year from the date of purchase. Should any problems arise, please contact your dealer. No warranty card is necessary.

ISACTRAILTBX/R1

7-17-08




Diagram 1.




Diagram 2.