

# ARCTIC CAT®

## FIRECAT SPORT PACK / BACKPACK

3639-176

Check for the following parts before beginning installation:  
Instruction sheet, Trunkbag/backpack, D-ring assemblies

Please follow instructions carefully!

### INSTALLATION INSTRUCTIONS-

Place bag on the back of the seat with the top of the bag even with the front of the seat hump.

Connect the shoulder strap buckles and attach the bridle strap with the hook to the tunnel/suspension support bracket. See fig. 1. For long track models- Using 1" D-ring assembly and rivets, measure and mark 5" centered forward of the seat hump. Using 3/16" drill bit, drill and pop rivet strap to the tunnel. This D-ring assembly will receive the plastic hook on the strap.

Pulling the bag back and tight against the bottom of the seat and taillight base. Connect the 1.5" strap with buckles under the rear bumper. Cinch tight. See fig. 2. For long track models- Using the 2" D-ring assembly and rivets, measure and mark 4" on center behind the rear seat on the footwell. Drill and pop rivet the strap. Feed and connect the rear buckles through the D-ring. See fig. 3.

FIGURE 1.



FIGURE 2.



FIGURE 3.



**DO NOT CARRY SHARP POINTED OR HEAVY OBJECTS!**

Weight limitation-5 lbs.

The bag can be disconnected and used as a backpack at owner's discretion. Excess webbings can be cut down and burnt, be sure that enough is left to accommodate shoulder and waist measurement.

There is a drawstring that can be cinched over the zipper to help in keeping articles dry.

When used as a backpack the shovel handle can be attached to the shovel and stored inside the exterior compartment of the bag connecting the velcro around the base.

When used as a trunk bag the shovel handle goes through the sleeve and is secured by a velcro wrap.

Using cinch straps, cinch bag tight around contents to keep articles from shifting. Adjust articles to prevent shifting.

\* Spare parts are available directly from: Commercial Sewing, 65 Grant St., Torrington, CT 06790 (860) 482-5509