

ARCTIC CAT[®]

TANK BAG WITH MAP HOLDER

Part #3639-710

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Tank Bag with Map Holder, 2 Pop rivets, 2 Webbing d-ring, 2 Washers

INSTALLATION INSTRUCTIONS

Place the bag in desired location on tank of snowmobile; just under the gas cap, and clear of the instrument panel.

On each side, pull straps slightly forward at an angle - down to tunnel. If you have a tank cover simply connect the plastic clips to the clips on the tank cover. If you do not have a tank cover, mark the location where the hole in the webbing aligns approximately even with the gas fill neck. Keep both sides symmetrical. This will pull the bag forward and snug to the gas neck.

Note where webbing/d-ring straps are to attach to the machine, then making sure there are no obstructions behind the drilling surface, drill a 1/8" hole at the center of each. **CAUTION:** Failure to inspect the area behind the drilling surface prior to drilling may result in damage to other snowmobile components.

Using pop rivets provided rivet the webbing straps to the tunnel. Be sure to go from the inside out and be sure to go through the washer.

Connect the straps on the bag to the riveted straps and secure.

WARNING: Do not carry sharp, pointed, or heavy objects. Maximum weight limit: 3 lbs.

This bag can be used in conjunction with tank jackets:

3639-700, 3639-701, 3639-702, 3639-703, 3639-704, 3639-705, 3639-706, 3639-707, 3639-908

Note: The map holder portion can be detached at owner's discretion. While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS3639710/R0

3-22-04

ARCTIC CAT[®]

TANK BAG WITH MAP HOLDER

Part #3639-710

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Tank Bag with Map Holder, 2 Pop rivets, 2 Webbing d-ring, 2 Washers

INSTALLATION INSTRUCTIONS

Place the bag in desired location on tank of snowmobile; just under the gas cap, and clear of the instrument panel.

On each side, pull straps slightly forward at an angle - down to tunnel. If you have a tank cover simply connect the plastic clips to the clips on the tank cover. If you do not have a tank cover, mark the location where the hole in the webbing aligns approximately even with the gas fill neck. Keep both sides symmetrical. This will pull the bag forward and snug to the gas neck.

Note where webbing/d-ring straps are to attach to the machine, then making sure there are no obstructions behind the drilling surface, drill a 1/8" hole at the center of each. **CAUTION:** Failure to inspect the area behind the drilling surface prior to drilling may result in damage to other snowmobile components.

Using pop rivets provided rivet the webbing straps to the tunnel. Be sure to go from the inside out and be sure to go through the washer.

Connect the straps on the bag to the riveted straps and secure.

WARNING: Do not carry sharp, pointed, or heavy objects. Maximum weight limit: 3 lbs.

This bag can be used in conjunction with tank jackets:

3639-700, 3639-701, 3639-702, 3639-703, 3639-704, 3639-705, 3639-706, 3639-707, 3639-908

Note: The map holder portion can be detached at owner's discretion. While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS3639710/R0

3-22-04