

Check for the following before beginning installation:

1 Instruction sheet, 1 Tank jacket with Pockets, 2 Self-adhesive Velcro

Note: Prior to installation your tank should be thoroughly cleaned! Failure to do so may result in dulling of the finish!

## INSTALLATION INSTRUCTIONS

Remove gas cap, and windshield screws.

Install filler neck through cover. Reinstall the gas cap. For the 12 gallon with a fuel gauge align the hole over the fuel gauge. For a 12 gallon tank without the fuel gauge place the supplied AC emblem under the hole.

Pull the bag down evenly. Note where the Velcro will attach to the tunnel. Check locations for symmetry on both sides.

Reinstall the windshield screws going through the plastic tabs on the jacket.

Clean the tunnel below the gas tank with isopropyl rubbing alcohol. When the tunnel is at room temp, attach the self-adhesive Velcro to the tunnel.

Connect the bag to the Velcro.

**CAUTION:** 

Weight limitation: 2 lbs. per pocket Do not carry sharp or pointed objects

IS4639133115/R0 3-11-05

## ARCTIC CAT®

TANK JACKET 12 gallon tank-4639-133 TANK JACKET 13 gallon tank-4639-115

Check for the following before beginning installation:

1 Instruction sheet, 1 Tank jacket with Pockets, 2 Self-adhesive Velcro

Note: Prior to installation your tank should be thoroughly cleaned! Failure to do so may result in dulling of the finish!

## INSTALLATION INSTRUCTIONS

Remove gas cap, and windshield screws.

Install filler neck through cover. Reinstall the gas cap. For the 12 gallon with a fuel gauge align the hole over the fuel gauge. For a 12 gallon tank without the fuel gauge place the supplied AC emblem under the hole.

Pull the bag down evenly. Note where the Velcro will attach to the tunnel. Check locations for symmetry on both sides.

Reinstall the windshield screws going through the plastic tabs on the jacket.

Clean the tunnel below the gas tank with isopropyl rubbing alcohol. When the tunnel is at room temp. attach the self-adhesive Velcro to the tunnel.

Connect the bag to the Velcro.

CAUTION: Weight limitation: 2 lbs. per pocket Do not carry sharp or pointed objects

IS4639133115/R0 3-11-05



TANK JACKET 12 gallon tank-4639-133 TANK JACKET 13 gallon tank-4639-115

Check for the following before beginning installation:

1 Instruction sheet, 1 Tank jacket with Pockets, 2 Self-adhesive Velcro

Note: Prior to installation your tank should be thoroughly cleaned! Failure to do so may result in dulling of the finish!

## INSTALLATION INSTRUCTIONS

Remove gas cap, and windshield screws.

Install filler neck through cover. Reinstall the gas cap. For the 12 gallon with a fuel gauge align the hole over the fuel gauge. For a 12 gallon tank without the fuel gauge place the supplied AC emblem under the hole.

Pull the bag down evenly. Note where the Velcro will attach to the tunnel. Check locations for symmetry on both sides.

Reinstall the windshield screws going through the plastic tabs on the jacket.

Clean the tunnel below the gas tank with isopropyl rubbing alcohol. When the tunnel is at room temp. attach the self-adhesive Velcro to the tunnel.

Connect the bag to the Velcro.

CAUTION: Weight limitation: 2 lbs. per pocket Do not carry sharp or pointed objects

IS4639133115/R0 3-11-05