Arctic Cat Snowmobile Installation Instructions

BAG, REAR RACK-09,BC XT 5639-049

■ NOTE: Read these instructions thoroughly and carefully before beginning the installation process. Retain these instructions for future reference.

FOR ALL APPLICATIONS:


- Thread the hooks to the adjustable buckles attached to the bag as seen
- in the illustration.

 2. Wrap the unused velcro/webbing strap to itself.

- FOR 2-UP seat (see photos 1&2)
 1. Place bag on the rack with the material pocket over the seat upright.
- 2. Wrap and connect the velcro around the bar at the end of the tunnel.
- 2. Thread the top hook under and around the passenger grab bar and attach the hook to the d-ring.
- Connect the bottom hook to the cut out in the bottom of the rack. Cinch hooks tight.

FOR The standard seat (See photo 3)

- 1. Lay the bag down in the rack.
- 2. Connect the velcro wrap to the bar at the end of the tunnel.
- 3. Connect the hooks to the underside of the running board where the quick release pin for the seat extension attaches. Cinch hooks tight.





CAUTION

Do not carry sharp or pointed objects. Maximum carrying capacity 25 lbs.











Printed in the U.S.A. S™Trademarks of Arctic Cat Inc., Thief River Falls, MN 56701