

Arctic Cat Snowmobile

Installation Instructions

06 Crossfire Tank Jacket
(p/n 4639-107, 108, & 109)

07 Crossfire Tank Jacket
(p/n 4639-435, 436, & 437)

■ **NOTE:** Read these instructions thoroughly and carefully before beginning the installation process. Retain these instructions for future reference.

Check for the following parts before beginning installation: Instruction sheet, Tank jacket, Self adhesive velcro

Note: Before installation your tank should be thoroughly cleaned. Failure to do so may result in dulling of the finish.

HINT: This cover is designed to fit very snug on your tank. It is best to install this item at room temperature. Please follow instructions carefully!

INSTALLATION INSTRUCTIONS

1. Open hood, remove gas cap, and seat.
2. Install filler neck through cover, and replace the gas cap.
3. Feed the bottom velcro strap through the metal slot inside the footwell closest to the round cut out on the top inside of the footwell. Feed the top velcro through the top louver vent and connect to the bottom velcro. (**Hint**-More tension is better to keep the front in place.) You may need to re-adjust these straps later to balance the tension between the front and the sides.
4. Clean the tunnel below the gas tank with isopropyl alcohol. When the tunnel is at room temp attach the 2"self adhesive velcro to the tunnel. Start approximately 1" behind the tank. Pull the cover down and rearward to attach to the velcro. Note the edge of the cover should tuck between the seat and the tank. Adjust velcro if necessary.
5. Close hood, and re-attach seat.



Printed in the U.S.A. ©™Trademarks of Arctic Cat Inc., Thief River Falls, MN 56701



0804

ISCROSSFIRETANK/R1

3-24-06

Arctic Cat Snowmobile

Installation Instructions

06 Crossfire Tank Jacket
(p/n 4639-107, 108, & 109)

07 Crossfire Tank Jacket
(p/n 4639-435, 436, & 437)

■ **NOTE:** Read these instructions thoroughly and carefully before beginning the installation process. Retain these instructions for future reference.

Check for the following parts before beginning installation: Instruction sheet, Tank jacket, Self adhesive velcro

Note: Before installation your tank should be thoroughly cleaned. Failure to do so may result in dulling of the finish.

HINT: This cover is designed to fit very snug on your tank. It is best to install this item at room temperature. Please follow instructions carefully!

INSTALLATION INSTRUCTIONS

1. Open hood, remove gas cap, and seat.
2. Install filler neck through cover, and replace the gas cap.
3. Feed the bottom velcro strap through the metal slot inside the footwell closest to the round cut out on the top inside of the footwell. Feed the top velcro through the top louver vent and connect to the bottom velcro. (**Hint**-More tension is better to keep the front in place.) You may need to re-adjust these straps later to balance the tension between the front and the sides.
4. Clean the tunnel below the gas tank with isopropyl alcohol. When the tunnel is at room temp attach the 2"self adhesive velcro to the tunnel. Start approximately 1" behind the tank. Pull the cover down and rearward to attach to the velcro. Note the edge of the cover should tuck between the seat and the tank. Adjust velcro if necessary.
5. Close hood, and re-attach seat.



Printed in the U.S.A. ©™Trademarks of Arctic Cat Inc., Thief River Falls, MN 56701



0804

ISCROSSFIRETANK/R1

3-24-06