ARCTIC CAT

Important Warranty Information

MARNING! FAILURE TO READ MAY CAUSE DAMAGE TO YOUR COVER OR MACHINE!

Your new Arctic Cat snowmobile cover has been carefully manufactured of the finest quality materials available. It has been designed specifically for winter use, featuring heavy duty, water resistant, mildew resistant canvas with safety ties for trailering. It is the only cover authorized by Arctic Cat for your new sled.


PROPER INSTALLATION

- 1. Place cover over windshield/handlebar area first, then secure over the front bumper and then the rear seat hump. Note: The reflective stripe or the silkscreen goes toward the front of the cover. Adjust the cover down to the tunnel. To remove; reverse the process.
- 2. Thread the hooks through the ladderlocks attached to the cover (See Diagram). Secure the hooks to the suspension and cinch tight. To release, lift gently on the tab of the adjuster buckle.
- 3. To tighten the cover, thread the long straps provided through the adjuster buckles near the center of the cover at the top, and tighten.

IMPORTANT SUMMER PROTECTION AFTER FINAL WINTER USE:

Hose down thoroughly both inside and out to remove all road salt and dirt. (Do NOT machine wash.) Dry on the machine or on the clothesline. (Do NOT machine dry.) Do not store machine in direct sun with this cover on. Either remove cover or shade machine and cover.

Prolonged exposure to intense sunlight, heat, and salt build-up can result in a breakdown of the cotton fibers in your cover. Damage due to prolonged exposure to direct sunlight cannot be warranteed.



WARRANTY

Your new Arctic Cat cover is guaranteed against defective material and workmanship for one full year from the date of your purchase. Should you have a problem of any kind, please contact your dealer. No warranty card is necessary. NOTE: Damage due to "whipping" is limited to cover replacement. Trailering at speeds in excess of the speed limit may cause damage to cover and/or sled.

IS639021678679/R1 9-4-05

ARCTIC CAT

Important Warranty Information

UNIVERSAL COVER

⚠ WARNING! FAILURE TO READ MAY CAUSE DAMAGE TO YOUR COVER OR MACHINE!

Your new Arctic Cat snowmobile cover has been carefully manufactured of the finest quality materials available. It has been designed specifically for winter use, featuring heavy duty, water resistant, mildew resistant canvas with safety ties for trailering. It is the only cover authorized by Arctic Cat for your new sled.

PROPER INSTALLATION

- 1. Place cover over windshield/handlebar area first, then secure over the front bumper and then the rear seat hump. Note: The reflective stripe or the silkscreen goes toward the front of the cover. Adjust the cover down to the tunnel. To remove; reverse the process.
- 2. Thread the hooks through the ladderlocks attached to the cover (See Diagram). Secure the hooks to the suspension and cinch tight. To release, lift gently on the tab of the adjuster buckle.
- 3. To tighten the cover, thread the long straps provided through the adjuster buckles near the center of the cover at the top, and tighten.

IMPORTANT SUMMER PROTECTION AFTER FINAL WINTER USE:

Hose down thoroughly both inside and out to remove all road salt and dirt. (Do NOT machine wash.) Dry on the machine or on the clothesline. (Do NOT machine dry.) Do not store machine in direct sun with this cover on. Either remove cover or shade machine and cover.

Prolonged exposure to intense sunlight, heat, and salt build-up can result in a breakdown of the cotton fibers in your cover. Damage due to prolonged exposure to direct sunlight cannot be warranteed.

Pull to Tighten Attached to cover Buckle

WARRANTY

Your new Arctic Cat cover is guaranteed against defective material and workmanship for one full year from the date of your purchase. Should you have a problem of any kind, please contact your dealer. No warranty card is necessary. NOTE: Damage due to "whipping" is limited to cover replacement. Trailering at speeds in excess of the speed limit may cause damage to cover and/or sled.

IS639021678679/R1 9-4-05