

# Kawasaki®

## CAMO SEAT COVER

Part #KLF220-A02C & #KLF220-A02M (For KLF 220A)  
#KLF300-B02C (For KLF 300B)  
#KLF340-002C & #KLF340-002M (For KLF 300C / 400B)  
#KVF400-002C & #KVF340-002M (For KVF 300A/B and KVF 400A/B/C/D)

### INSTALLATION INSTRUCTIONS

1. Remove seat as per instruction manual.
2. Disconnect buckles and place elasticized cover over seat.
3. Reconnect buckles and cinch tight.
4. Reinstall seat.

### CAUTION:

During installation, be sure to stay clear of any moving components or electrical wires.

### WARNING:

Do not store the ATV outdoors with the seat cover installed. Direct long term exposure to sunlight may result in fading. Damage resulting from exposure to direct sunlight cannot be warrantied.

### WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for one year from date of purchase.

ISCAMOSEAT/R1

3-10-00

# Kawasaki®

## CAMO SEAT COVER

Part #KLF220-A02C & #KLF220-A02M (For KLF 220A)  
#KLF300-B02C (For KLF 300B)  
#KLF340-002C & #KLF340-002M (For KLF 300C / 400B)  
#KVF400-002C & #KVF340-002M (For KVF 300A/B and KVF 400A/B/C/D)

### INSTALLATION INSTRUCTIONS

1. Remove seat as per instruction manual.
2. Disconnect buckles and place elasticized cover over seat.
3. Reconnect buckles and cinch tight.
4. Reinstall seat.

### CAUTION:

During installation, be sure to stay clear of any moving components or electrical wires.

### WARNING:

Do not store the ATV outdoors with the seat cover installed. Direct long term exposure to sunlight may result in fading. Damage resulting from exposure to direct sunlight cannot be warrantied.

### WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for one year from date of purchase.

ISCAMOSEAT/R1

3-10-00