

Part #KAF30-015, #KAF300-18, #KAF300-25, & #KAF300-26

### INSTALLATION INSTRUCTIONS

- 1. Thread all buckles from the sub-assembly kit to the bottom of the enclosure. \*\*\* On Mule 4000 series thread the center straps with the hook facing outward.
- 2. With the dump body in the downward position, fit the frame bars together being sure they are of equal height and that the pre-drilled holes are facing the same direction. Secure together with screws where the two pieces come together. Place the taller frame in the front cutouts of the dump body, place the shorter frame in the rear cutouts of the dump body, be sure that pre-drilled holes are all facing to the inside of the dump body.
- 3. Place the two straight rods in the two side brackets. Place the curved rod in the top bracket. The curve goes toward the top. Use the screws in the brackets.
- 4. Using caution to stand clear of the hooks, drape the unzipped enclosure over the frame with the smallest clear window in the enclosure facing forward. Center the unit so that it fits evenly on all sides.
- 5. Attach all hooks to the bottom of the dump body. \*\*\*On Mule 4000 series attach the two side center hooks by slightly pulling the fender away to get the hook past the fender and attach the hook to the horizontal steel rod inside the fender. Cinch all hooks evenly. Zipper both the sides and the back closed.

# A WARNING!

Before operating it is suggested to check all connections and secure as necessary.

Do not operate in temps below -30

Remove if unit is to be trailered on public roads.

Do not operate unit without window flaps rolled up.

## OPTIONAL

At operators discretion the sides or flaps can be rolled up. To do so, unlatch only the necessary tiedown hooks, roll and connect with velcro.

#### **CARE & CLEANING**

Do not machine wash or dry. To clean, hose down thoroughly to remove all dirt. Dry on machine or on a clothesline.

Do not store the Mule outdoors with the accessory installed. Prolonged exposure to direct sunlight and heat can result in a breakdown of the fibers in your cover. Damage resulting from prolonged exposure to direct sunlight cannot be warrantied.

### WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for one year from date of purchase.

ISKAF300-15/R2 7-23-08