

Kawasaki®

SEAT BAG

Part #KVF650-140, 142, 143, & KVF750-026

INSTALLATION INSTRUCTIONS

1. Remove seat, as per instruction manual.
2. Fit seat bag on rear of seat, making sure it is centered and pulled tight.
3. Note and center punch the seat at the location of the female snap.
4. Drill size #28 hole in seat and screw in male snap making sure not to strip the hole.
5. Attach the seat bag.
6. Reinstall seat.

CARE & CLEANING

Do not machine wash or dry. To clean, hose down thoroughly to remove all dirt and/or road salt. Dry bags on machine or on a clothesline.

Do not store the ATV outdoors with this bag installed. Prolonged exposure to direct sunlight, heat and salt build-up can result in a breakdown of the cotton fibers in your accessory. Damage resulting from exposure to direct sunlight cannot be warranted.

WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for 90 days from date of purchase.

ISKVF650140/42/43/R2

1-6-06

Kawasaki®

SEAT BAG

Part #KVF650-140, 142, 143, & KVF750-026

INSTALLATION INSTRUCTIONS

1. Remove seat, as per instruction manual.
2. Fit seat bag on rear of seat, making sure it is centered and pulled tight.
3. Note and center punch the seat at the location of the female snap.
4. Drill size #28 hole in seat and screw in male snap making sure not to strip the hole.
5. Attach the seat bag.
6. Reinstall seat.

CARE & CLEANING

Do not machine wash or dry. To clean, hose down thoroughly to remove all dirt and/or road salt. Dry bags on machine or on a clothesline.

Do not store the ATV outdoors with this bag installed. Prolonged exposure to direct sunlight, heat and salt build-up can result in a breakdown of the cotton fibers in your accessory. Damage resulting from exposure to direct sunlight cannot be warranted.

WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for 90 days from date of purchase.

ISKVF650140/42/43/R2

1-6-06