

# Kawasaki®

## TRANS 4 SEAT COVER

### INSTALLATION INSTRUCTIONS

1. Refer to the sewn in label to match and arrange the appropriate seat cover with the appropriate portion of the seat.
2. **For the front bench seat:** Tilt the seat bottom forward. Pull the elasticized edge of the seat cover over the seat. Connect the velcro.
3. **For the front seat backrest:** Place the material over the backrest, align the cut outs and connect the webbing straps. Connect the velcro.
4. **For the rear bench seat:** Tilt the seat bottom forward. Pull the elasticized edge of the cover over the edges of the seat aligning the cut outs. Connect the snaps and connect the webbing straps in a criss-cross formation.
5. **For the rear seat backrest:** Place the elasticized edge of the cover over the edge of the seat. Connect the snaps and the webbing straps.



### CARE & CLEANING

Do not machine wash or dry. To clean, hose down thoroughly to remove all dirt. Dry cover on machine or on a clothesline. Do not store the ATV outdoors with the accessory installed. Prolonged exposure to direct sunlight and heat can result in a breakdown of the fibers in your cover. Damage resulting from prolonged exposure to direct sunlight cannot be warranted.

### WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for 90 days from date of purchase.

ISTRANS4SEATRO

2-8-08

# Kawasaki®

## TRANS 4 SEAT COVER

### INSTALLATION INSTRUCTIONS

1. Refer to the sewn in label to match and arrange the appropriate seat cover with the appropriate portion of the seat.
2. **For the front bench seat:** Tilt the seat bottom forward. Pull the elasticized edge of the seat cover over the seat. Connect the velcro.
3. **For the front seat backrest:** Place the material over the backrest, align the cut outs and connect the webbing straps. Connect the velcro.
4. **For the rear bench seat:** Tilt the seat bottom forward. Pull the elasticized edge of the cover over the edges of the seat aligning the cut outs. Connect the snaps and connect the webbing straps in a criss-cross formation.
5. **For the rear seat backrest:** Place the elasticized edge of the cover over the edge of the seat. Connect the snaps and the webbing straps.



### CARE & CLEANING

Do not machine wash or dry. To clean, hose down thoroughly to remove all dirt. Dry cover on machine or on a clothesline. Do not store the ATV outdoors with the accessory installed. Prolonged exposure to direct sunlight and heat can result in a breakdown of the fibers in your cover. Damage resulting from prolonged exposure to direct sunlight cannot be warranted.

### WARRANTY INFORMATION

Your new Kawasaki accessory is guaranteed to be free from defects in material and workmanship for 90 days from date of purchase.

ISTRANS4SEATRO

2-8-08