



RANGER SOFT TOP Part #2872387

## INSTALLATION INSTRUCTIONS

1. Place fiberglass rod into holes in gray plastic clips, then snap the clips on the top center of the roll cage, slitting the foam if necessary, so that the rod is centered side to side and goes front to back .
2. Thread all male end buckles from sub-assembly kit onto corresponding straps, as shown in illustration.
3. Evenly drape top over frame of operators compartment so that the clear vinyl faces the back side.
4. Feed front webbing and buckle straps through front grab bars. Connect buckles, being sure to leave excess slack in webbing.
5. Feed top rear webbing and buckle straps through the frame post that falls behind the headrest. Connect buckles, being sure to leave excess slack in webbing.
6. Feed bottom rear webbing and buckle straps through main frame post and under post with warning decal. Connect buckles, being sure to leave excess slack in webbing.
7. Wrap and connect velcro pieces around cargo box dump latch.
8. Cinch all webbing and buckle straps evenly, being sure to keep top centered. The forward center strap should be pulled under the forward upper bar then back into the buckle.
9. Note where side velcro piece falls at main frame post. Peel backing of self-adhesive velcro and attach to noted area. This should be done at room temperature (70°F). Maximum velcro adhesion will occur in 24 hrs.

## CARE & CLEANING

To clean, simply rinse in cold water and allow to air dry.  
Do not use harsh detergents, do not machine wash or dry.

## WARNING!

Do not use in temperatures lower than -30°F.  
Remove if unit is to be trailered on public roads.  
Do not allow snow or water to accumulate be sure to install anti-pooling rod.

## OPTIONAL

Your Soft Top is equipped with a clear window. At your own discretion, the window can be disconnected and rolled up. Be sure that both rear sides are disconnected completely before attempting to roll up. Roll the window evenly. Velcro wraps are located at the top of the frame to secure rolled window.

## WARRANTY INSTRUCTIONS

Your new Polaris accessory is guaranteed by Polaris against any defects in material and workmanship for one full year from the date of purchase. Should any problems arise, please contact your dealer. No warranty card is necessary.

