



DELUXE TANK BAG with MAP HOLDER & POCKETS

Part #2873228, #2873229, #2873230, & #2873789 - Gen II/Evolved with 1 piece seat

Part #2873231, #2873232, #2873233, & #2873790 - Edge/Gen II with 2 piece seat

Your new Polaris® Tank Bag is carefully manufactured by Commercial Sewing, Inc. It has been designed and tested in cooperation with Polaris®.

WARRANTY: Your new Polaris® Tank Bag is guaranteed by Polaris® against any defects in material and workmanship for one full year from the date of your purchase. Should any problems arise with your new Tank Bag, please contact your dealer, for repair or replacement. No warranty card is necessary.

CARE: Simply sponge wash with warm, soapy water and rinse.
Maximum carrying capacity: 3 lbs.

INSTALLATION INSTRUCTIONS:

1. Place accessory over the tank, with the gas cap off. (Then replace gas cap.)
2. Pull the cover **tightly** down over the front edge of the tank.
3. Mark where snaps are to be located.
4. Using a 1/8" drill bit, drill the tunnel and install snap posts with the pop rivets provided.

Optional: For a more finished look, tuck front edge under dash console using a smooth piece of wood or a **blunt** screwdriver.

* Spare parts are directly available from Commercial Sewing, Inc. , 65 Grant St., Torrington, CT 06790 (860) 482-5509

IS2873228/3231/R2

4-1-02



DELUXE TANK BAG with MAP HOLDER & POCKETS

Part #2873228, #2873229, #2873230, & #2873789 - Gen II/Evolved with 1 piece seat

Part #2873231, #2873232, #2873233, & #2873790 - Edge/Gen II with 2 piece seat

Your new Polaris® Tank Bag is carefully manufactured by Commercial Sewing, Inc. It has been designed and tested in cooperation with Polaris®.

WARRANTY: Your new Polaris® Tank Bag is guaranteed by Polaris® against any defects in material and workmanship for one full year from the date of your purchase. Should any problems arise with your new Tank Bag, please contact your dealer, for repair or replacement. No warranty card is necessary.

CARE: Simply sponge wash with warm, soapy water and rinse.
Maximum carrying capacity: 3 lbs.

INSTALLATION INSTRUCTIONS:

1. Place accessory over the tank, with the gas cap off. (Then replace gas cap.)
2. Pull the cover **tightly** down over the front edge of the tank.
3. Mark where snaps are to be located.
4. Using a 1/8" drill bit, drill the tunnel and install snap posts with the pop rivets provided.

Optional: For a more finished look, tuck front edge under dash console using a smooth piece of wood or a **blunt** screwdriver.

* Spare parts are directly available from Commercial Sewing, Inc. , 65 Grant St., Torrington, CT 06790 (860) 482-5509

IS2873228/3231/R2

4-1-02
