

## SWITCHBACK SEMI-RIGID BAG PARTS LIST: TRUNK BAG, INSTRUCTION SHEET INSTALLATION INSTRUCTIONS-

Place the bag at the end of the close off behind the rack.

Connect the rear straps around the bumper.

Connect the front buckle straps around the rack handles.

Cinch the straps by pulling the end of the strap away from the bag and then away from the buckle.

Maximum carrying capacity 7.5 lbs.

ISSWITCHTRUNK/R1 5/8/06



## SWITCHBACK SEMI-RIGID BAG PARTS LIST: TRUNK BAG, INSTRUCTION SHEET INSTALLATION INSTRUCTIONS-

Place the bag at the end of the close off behind the rack.

Connect the rear straps around the bumper.

Connect the front buckle straps around the rack handles.

Cinch the straps by pulling the end of the strap away from the bag and then away from the buckle.

Maximum carrying capacity 7.5 lbs.

ISSWITCHTRUNK/R1 5/8/06



## SWITCHBACK SEMI-RIGID BAG PARTS LIST: TRUNK BAG, INSTRUCTION SHEET INSTALLATION INSTRUCTIONS-

Place the bag at the end of the close off behind the rack.

Connect the rear straps around the bumper.

Connect the front buckle straps around the rack handles.

Cinch the straps by pulling the end of the strap away from the bag and then away from the buckle.

Maximum carrying capacity 7.5 lbs.

ISSWITCHTRUNK/R1 5/8/06