

**INSTALLATION INSTRUCTIONS**  
**Camo Seat Cover Set**  
**43P-F47B0-V0**  
**Grizzly 700**



**⚠ WARNING**

Please read and understand these instructions completely before installation to avoid possible injury to yourself or damage to the accessory or vehicle.

**DEALER:**

These instructions contain important information for future reference and *must* be given to the customer.

**WARRANTY INFORMATION:**

- Genuine Yamaha accessories are covered by a one year limited warranty against defects in material or workmanship. Labor for replacement of defective components is not covered. See your Yamaha dealer for a copy of the warranty statement.
- The Limited Warranty provided with new Yamaha vehicles has exclusions for certain failures, including those caused by competition or racing use (except YZ and WR motorcycle models) as well as by abnormal strain or abuse. While installation of these components will not “void” your vehicle’s warranty, specific failures adjudged by Yamaha to have resulted from the installation of accessory components or other modifications, or from competition use (except YZ and WR motorcycle models), may not be covered by warranty or Yamaha Extended Service.


**PARTS LIST:**

This kit contains the following components. Before beginning installation, confirm there are no missing or damaged components.

Item	Part Number	Description	Qty
--	43P-F47B0-V0	Camo Seat Cover Set	--
①	*	Seat Cover	1

\* Part supplied with kit only and not available separately.

①



**Fig. 1**



**PREPARATION:**

1. Place ATV on a secure level surface and set the parking brake.
2. Clean all mounting surfaces before beginning installation.
3. Remove the rider's seat (refer to Owner's or Service Manual).

**INSTALLATION:**

1. Place the cover ① over the front part of the seat.
2. Pull the cover ① towards the rear part of the seat and around the bottom lip of each corner (Fig. 1).
3. Connect the Velcro straps under the seat (Fig. 1).
4. Reinstall the rider's seat.

**CARE AND CLEANING:**

Do not machine wash or dry. Hand wash using only cold water. Avoid using harsh detergents. Hang to dry.

**CUSTOMER SERVICE:**

For further information, see your Yamaha dealer.

**ESTIMATED TIME TO INSTALL: 0.1 HRS**