

# ARCTIC CAT®


## ATV FENDER BAG

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Fender Bag

### INSTALLATION INSTRUCTIONS

1. Place bag on driver's right hand side fender. (Where there are no warning labels.)
2. Feed the webbing/buckle strap around the rack bar. Connect the buckles.
3. Note where the webbing with the hook falls on the footwell. Connect the hook to the footwell and cinch tight.
4. Note where self-adhesive velcro on the underside of the bag falls on the fender. Remove bag and clean noted area with isopropyl rubbing alcohol and allow to dry.
5. Peel backing of self-adhesive velcro and adhere to area. Maximum velcro adhesion will occur in 24 hrs. at room temp. Re-install bag

 Do not carry sharp, heavy, or pointed objects. Maximum carrying capacity is 3 lbs.  
Do not store in direct sunlight! Direct long term exposure will cause pre-mature fading of the bag. Damage resulting from direct long term exposure can not be warranted.

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS043667984/R1

4-7-05

# ARCTIC CAT®


## ATV FENDER BAG

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Fender Bag

### INSTALLATION INSTRUCTIONS

1. Place bag on driver's right hand side fender. (Where there are no warning labels.)
2. Feed the webbing/buckle strap around the rack bar. Connect the buckles.
3. Note where the webbing with the hook falls on the footwell. Connect the hook to the footwell and cinch tight.
4. Note where self-adhesive velcro on the underside of the bag falls on the fender. Remove bag and clean noted area with isopropyl rubbing alcohol and allow to dry.
5. Peel backing of self-adhesive velcro and adhere to area. Maximum velcro adhesion will occur in 24 hrs. at room temp. Re-install bag

 Do not carry sharp, heavy, or pointed objects. Maximum carrying capacity is 3 lbs.  
Do not store in direct sunlight! Direct long term exposure will cause pre-mature fading of the bag. Damage resulting from direct long term exposure can not be warranted.

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS043667984/R1

4-7-05

# ARCTIC CAT®


## ATV FENDER BAG

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Fender Bag

### INSTALLATION INSTRUCTIONS

1. Place bag on driver's right hand side fender. (Where there are no warning labels.)
2. Feed the webbing/buckle strap around the rack bar. Connect the buckles.
3. Note where the webbing with the hook falls on the footwell. Connect the hook to the footwell and cinch tight.
4. Note where self-adhesive velcro on the underside of the bag falls on the fender. Remove bag and clean noted area with isopropyl rubbing alcohol and allow to dry.
5. Peel backing of self-adhesive velcro and adhere to area. Maximum velcro adhesion will occur in 24 hrs. at room temp. Re-install bag

 Do not carry sharp, heavy, or pointed objects. Maximum carrying capacity is 3 lbs.  
Do not store in direct sunlight! Direct long term exposure will cause pre-mature fading of the bag. Damage resulting from direct long term exposure can not be warranted.

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

IS043667984/R1

4-7-05