

ARCTIC CAT[®]

ATV TRAILERABLE COVER

0436-437, 0436-776, 1436-091

INSTALLATION:

1. Loosen all straps and buckles.
2. Place cover on the machine, handlebars first with the small "U" cut out facing the front.
3. Attach the front webbing.
4. Connect the front straps first by feeding the straps underneath the machine and then connecting them to the buckles on the side of the cover. Pull tight to eliminate any slack that is in the webbing, while doing so, be sure the cover stays centered.
5. Feed the rear webbing through the loop in the rear and connect the front and rear strap under any vehicle tie down straps. Tighten webbings making sure the cover is as low as possible on the tires and the cover doesn't rotate while tightening.
6. Thread the center webbing straps through the buckles in the top of the cover, cinch tight.

WARNING:

Do not trail your ATV with the cover installed on the trailer sideways or backwards.

Do not allow machine to roll or shift with cover on.

Do not touch cover or webbings to hot components.

CARE AND CLEANING

Do not machine wash or dry. To clean, hose down thoroughly both inside and out to remove all road salt and dirt. Dry cover installed on the machine or on the clothesline. Do not store machine in direct sunlight with this cover on. Either remove cover or shade machine and cover. Prolonged exposure to direct sunlight, heat and salt build-up can result in a breakdown of the cotton fibers in your cover. Damage due to prolonged exposure to direct sunlight cannot be warrantied.

WARRANTY INFORMATION

Your new cover is guaranteed to be free from defects in material and workmanship for one year from date of purchase.

IS0436437/R2

5-8-07

ARCTIC CAT[®]

ATV TRAILERABLE COVER

0436-437, 0436-776, 1436-091

INSTALLATION:

1. Loosen all straps and buckles.
2. Place cover on the machine, handlebars first with the small "U" cut out facing the front.
3. Attach the front webbing.
4. Connect the front straps first by feeding the straps underneath the machine and then connecting them to the buckles on the side of the cover. Pull tight to eliminate any slack that is in the webbing, while doing so, be sure the cover stays centered.
5. Feed the rear webbing through the loop in the rear and connect the front and rear strap under any vehicle tie down straps. Tighten webbings making sure the cover is as low as possible on the tires and the cover doesn't rotate while tightening.
6. Thread the center webbing straps through the buckles in the top of the cover, cinch tight.

WARNING:

Do not trail your ATV with the cover installed on the trailer sideways or backwards.

Do not allow machine to roll or shift with cover on.

Do not touch cover or webbings to hot components.

CARE AND CLEANING

Do not machine wash or dry. To clean, hose down thoroughly both inside and out to remove all road salt and dirt. Dry cover installed on the machine or on the clothesline. Do not store machine in direct sunlight with this cover on. Either remove cover or shade machine and cover. Prolonged exposure to direct sunlight, heat and salt build-up can result in a breakdown of the cotton fibers in your cover. Damage due to prolonged exposure to direct sunlight cannot be warrantied.

WARRANTY INFORMATION

Your new cover is guaranteed to be free from defects in material and workmanship for one year from date of purchase.

IS0436437/R2

5-8-07