

# ARCTIC CAT<sup>®</sup>

## BEARCAT GEAR BAG

Fits Part #3639-187

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Bearcat Gear Bag

### INSTALLATION WITH REAR PASSENGER SEAT REMOVED

1. Place bag laying down in rack with the Arctic Cat patch facing the rear of the machine.
2. Attach rear velcro wraps around plastic frame near taillight. Thread front velcro wraps through backrest adjustment slot.

### INSTALLATION WITH REAR PASSENGER SEAT INSTALLED

1. Place bag standing upright in the rack, with the zippered opening facing the rear of the machine.
2. Attach lower velcro wraps around rack frame and metal. Route the long upper velcro straps between the backrest pad and backrest adjustment arms; then secure velcro straps to bag. When not in use attach the webbing to the lower loop velcro.

**⚠ Caution:** For heavy loads or rough terrain it is recommended you use additional tie-downs such as bungee cord or rope. Attach handles across zippered opening when being used in the rack.

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

**Do not carry sharp or heavy objects, maximum carrying capacity is 15 lbs.**

IS3639187/R0

7-15-03

# ARCTIC CAT<sup>®</sup>

## BEARCAT GEAR BAG

Fits Part #3639-187

Check for the following parts before beginning installation:

1 Instruction sheet, 1 Bearcat Gear Bag

### INSTALLATION WITH REAR PASSENGER SEAT REMOVED

1. Place bag laying down in rack with the Arctic Cat patch facing the rear of the machine.
2. Attach rear velcro wraps around plastic frame near taillight. Thread front velcro wraps through backrest adjustment slot.

### INSTALLATION WITH REAR PASSENGER SEAT INSTALLED

1. Place bag standing upright in the rack, with the zippered opening facing the rear of the machine.
2. Attach lower velcro wraps around rack frame and metal. Route the long upper velcro straps between the backrest pad and backrest adjustment arms; then secure velcro straps to bag. When not in use attach the webbing to the lower loop velcro.

**⚠ Caution:** For heavy loads or rough terrain it is recommended you use additional tie-downs such as bungee cord or rope. Attach handles across zippered opening when being used in the rack.

**Note:** While your new Arctic Cat accessory is water resistant, it is not waterproof. It is recommended that items which must be kept dry be placed in a plastic bag or container before loading.

**Do not carry sharp or heavy objects, maximum carrying capacity is 15 lbs.**

IS3639187/R0

7-15-03