

INSTALLATION INSTRUCTIONS MOTORCYCLE COVER ABA-4C828-00-XX 2007 YZF-R1



♠WARNING

Please read and understand these instructions completely before installation to avoid possible injury to yourself, or damage to the accessory or vehicle.

CAUTION:

- This installation should be performed by an authorized Yamaha dealer or a qualified mechanic. Some
 components require information from the model's service manual for proper installation or adjustment.
 Be sure to have the service manual on hand, if necessary, before proceeding with the installation.
- Alteration of emission-related components constitutes tampering under Federal and State laws and can lead to substantial fines and penalties if used other than in closed-course competition.
- Engine-related competition parts are intended for closed-course racing applications only.

DEALER:

These instructions contain important information for future reference and *must* be given to the customer.

WARRANTY INFORMATION:

- Genuine Yamaha components are covered by a 90-day warranty against defects in material or workmanship. Labor for replacement of defective components is not covered. See your Yamaha dealer for a copy of the warranty statement.
- The Limited Warranty provided with new Yamaha vehicles has exclusions for certain failures, including those caused by competition or racing use (except YZ and WR motorcycle models) as well as by abnormal strain or abuse. While installation of these components will not "void" your vehicle's warranty, specific failures adjudged by Yamaha to have resulted from the installation of accessory components or other modifications, or from competition use (except YZ and WR motorcycle models), may not be covered by warranty or Yamaha Extended Service.

1. PARTS LIST:

This kit contains the following components. Before beginning installation confirm there are no missing or damaged components.

Γ	Item #	Part Number	Description	Qty
	1	ABA-4C828-00-XX	Bike Cover	1



2. PREPARATION:

- Place motorcycle on a secure stand.
- Clean all dust, grease and road grime from motorcycle before installing cover.

♠WARNING

Do not install cover until vehicle has cooled to the touch. Hot engine or exhaust parts could cause burns or damage the cover. Keep cover away from flame or other sources of ignition. Do not use motorcycle cover in high wind areas, as the cover can cause the motorcycle to tip over.

3. INSTALLATION:

- If vehicle will not be operated for an extended period of time, be sure to take appropriate storage measures.
- Be sure vehicle has sufficiently cooled, then install cover over vehicle making certain that R1 logo is located towards the front of motorcycle as shown in item #1.
- Be sure that the heat-resistant double lined section covers the muffler areas.
- Once cover is correctly installed, cinch the drawstring around the bottom of cover and secure
 with the plastic push-lock, which is located at the rear of the motorcycle.

N	т	
IV		_

The loops located on the bottom perimeter (left and right) of motorcycle cover, allow user to secure a cable lock (not included) to motorcycle.

4. MAINTENANCE:

Avoid temperature extremes, direct sunlight and keep away from moisture whenever possible to preserve the fit and finish of the motorcycle cover.

5. CARE AND CLEANING:

Hand wash using a mild soap and water solution. Hang dry.

6. CUSTOMER SERVICE:

For further information see your Yamaha dealer.