

INSTALLATION INSTRUCTIONS
MOTORCYCLE COVER
ABA-2D228-00-XX
2006/2007 FJR1300



⚠ WARNING

Please read and understand these instructions completely before installation to avoid possible injury to yourself, or damage to the accessory or vehicle.

CAUTION:

- This installation should be performed by an authorized Yamaha dealer or a qualified mechanic. Some components require information from the model's service manual for proper installation or adjustment. Be sure to have the service manual on hand, if necessary, before proceeding with the installation.
- Alteration of emission-related components constitutes tampering under Federal and State laws and can lead to substantial fines and penalties if used other than in closed-course competition.
- Engine-related competition parts are intended for closed-course racing applications only.

DEALER:

These instructions contain important information for future reference and *must* be given to the customer.

WARRANTY INFORMATION:

- Genuine Yamaha components are covered by a 90-day warranty against defects in material or workmanship. Labor for replacement of defective components is not covered. See your Yamaha dealer for a copy of the warranty statement.
- The Limited Warranty provided with new Yamaha vehicles has exclusions for certain failures, including those caused by competition or racing use (except YZ and WR motorcycle models) as well as by abnormal strain or abuse. While installation of these components will not "void" your vehicle's warranty, specific failures adjudged by Yamaha to have resulted from the installation of accessory components or other modifications, or from competition use (except YZ and WR motorcycle models), may not be covered by warranty or Yamaha Extended Service.

1. PARTS LIST:

This kit contains the following components. Before beginning installation confirm there are no missing or damaged components.

Item #	Part Number	Description	Qty
1	ABA-2D228-00-XX	Bike Cover	1

Item #1





PREPARATION:

- Place motorcycle on a secure stand.
- Clean all dust, grease and road grime from motorcycle before installing cover.

⚠WARNING

Do not install cover until vehicle has cooled to the touch. Hot engine or exhaust parts could cause burns or damage the cover. Keep cover away from flame or other sources of ignition.

2. INSTALLATION:

- Be sure vehicle has sufficiently cooled, then install cover over vehicle. It is easier to start with the front of the vehicle and work the cover over the rear.
- Be sure heat-resistant reflective lining covers muffler area.
- If vehicle will not be operated for an extended period of time, be sure to take appropriate storage measures.

3. MAINTENANCE:

Avoid temperature extremes and keep away from moisture whenever possible.

4. CARE AND CLEANING:

Wash using a mild soap and water solution. Hang dry.

5. CUSTOMER SERVICE:

For further information see your Yamaha dealer.