



Parts & Accessories

Please read and understand the instructions completely before installation to avoid any possible injury to yourself or damage to the accessory or your snowmobile.

DEALER: These instructions contain important information for future reference and must be given to the customer.

1. PARTS LIST:

ITEM	PART NAME	DESCRIPTION	QTY.
1	INSTRUCTION SHEET	PAPER	1
2	YAMAHA TANK BAG	BALLISTIC NYLON	1

Study the illustrations thoroughly before proceeding.

2. INSTALLATION:

- Remove the gas cap and place the tank bag on the tank. Place the webbing loop around the neck of the gas tank and replace the gas cap.
- For the 1-up place the plastic between the end of the seat and the plastic. See photo 1.
For the 2-up either remove the plastic by cutting the stitches or lay the plastic flat with the soft velcro on the tank.
- Attach the male and female side release buckles feeding the webbing around the bar in the footwell as seen in photo 2.



Photo 1.



Photo 2.

3. LOADING CONSIDERATIONS:

- NEVER OVERLOAD the accessory. The LOAD LIMIT is 2 lbs.
 - While your new accessory is water resistant it is not waterproof. In extreme conditions or with items that must be kept completely dry we suggest storing them in a plastic bag.
 - DO NOT carry sharp, pointed or heavy objects.
4. CARE & CLEANING: Use a "Vacuum cleaner", sponge or cloth and clean water. Do not use detergents or harsh chemicals.

5. CUSTOMER SERVICE: See your YAMAHA dealer.
ISPHAZERTANKBAG/R0

3-15-06



Parts & Accessories

Please read and understand the instructions completely before installation to avoid any possible injury to yourself or damage to the accessory or your snowmobile.

DEALER: These instructions contain important information for future reference and must be given to the customer.

1. PARTS LIST:

ITEM	PART NAME	DESCRIPTION	QTY.
1	INSTRUCTION SHEET	PAPER	1
2	YAMAHA TANK BAG	BALLISTIC NYLON	1

Study the illustrations thoroughly before proceeding.

2. INSTALLATION:

- Remove the gas cap and place the tank bag on the tank. Place the webbing loop around the neck of the gas tank and replace the gas cap.
- For the 1-up place the plastic between the end of the seat and the plastic. See photo 1.
For the 2-up either remove the plastic by cutting the stitches or lay the plastic flat with the soft velcro on the tank.
- Attach the male and female side release buckles feeding the webbing around the bar in the footwell as seen in photo 2.




Photo 1.



Photo 2.

3. LOADING CONSIDERATIONS:

- NEVER OVERLOAD the accessory. The LOAD LIMIT is 2 lbs.
 - While your new accessory is water resistant it is not waterproof. In extreme conditions or with items that must be kept completely dry we suggest storing them in a plastic bag.
 - DO NOT carry sharp, pointed or heavy objects.
4. CARE & CLEANING: Use a "Vacuum cleaner", sponge or cloth and clean water. Do not use detergents or harsh chemicals.

5. CUSTOMER SERVICE: See your YAMAHA dealer.
ISPHAZERTANKBAG/R0

3-15-06