

Installation Instructions YAMAHA BIMINI EXTENSION

Please read and understand the instructions completely before installation to avoid any possible injury to yourself or damage to the accessory.

DEALER: These instructions contain important information for future reference and must be given to the customer.

1. PARTS LIST:

ITEM	PART NAME	QTY
1	INSTRUCTION SHEET	1
2	YAMAHA BIMINI EXTENSION	1
3	SNAP LOOPS	2
4	SCREWS	8
5	ACCON INSERTS	2
6	MIDDLE POLE	1
7	SIDE POLE	2

Study the illustrations on the following page thoroughly before proceeding.

The instructions must be followed in the order specified below.

2. INSTALLATION:

FRAME INSTALLATION:

At the rear of the bimini, zip the end of the bimini extension to the bimini.

Matching up the color on the side poles with the color on the center pole, connect middle pole to side poles and insert into sewn sleeve of the bimini extension.

Tape and pre-drill 1/8" holes to install the snap loops.

BIMINI EXTENSION INSTALLATION:

Mark the location of the aacon insert approx. 15" from the foot of the cleat to the rear hole of the aacon insert. See pic. 1. Tape and pre-drill 1/8" hole and install aacon insert. Connect the quick release end of the bimini to the aacon insert.

Measure for the footmans loop location approx. 13" from the rear cleat foot to the front of the footmans loop. Pre-drill 1/8" hole and install footmans loop. See pic. 2.

Connect the snap hook on the webbing to the footmans loop.

